

Covering:

Roof: 26 Gauge, PR Panels, Color: Galvalume
 Sidewall: 26 Gauge, PR Panels, Color: NEED COLOR
 Endwall: 26 Gauge, PR Panels, Color: NEED COLOR
 Sidewall trim at eave : NEED COLOR
 Endwall (rake) trim at roof : Galvalume
 Outside jamb sheeting trim color: NEED COLOR
 Outside corner trim color : NEED COLOR

Framing:

----- Interior -----

3 rigid frames, clear span
 Frame Design Id Column Type Rafter Type

 1 tapered depth tapered depth

Spacing along front sidewall: 3 at 20

----- Exterior Walls -----

Endwall: Left = Rigid, Flush girts
 Right = Bearing, Flush girts
 Sidewall: Front = Bypass
 Back = Bypass

----- Wind -----

Roof: Cable Diagonal Bracing
 Endwall: Left = Rigid Frame
 Right = Panel Shear
 Sidewall: Front = Cable Diagonal Bracing
 Back = Cable Diagonal Bracing

----- Factory Located Framed Openings -----

Factory Located Framed Openings:
 Left Endwall : 34' x 18' clear hangar door opening
 Front Sidewall : none
 Right Endwall : none
 Back Sidewall : none

Gutters and Downspouts:

Front sidewall gutters(ft): none
 Front sidewall downspouts: none
 Back sidewall gutters(ft): none
 Back sidewall downspouts: none

=====

OPTIONAL ITEMS

=====

Walk Doors: 1 - 3070MI

Translucent Wall Panels: none

Translucent Roof Panels: none

Insulation:

Roof: WMP-VR, 2 inch
 Wall: WMP-VR, 2 inch

Delivered Weight: 21024.9 lbs

